



TECHNICAL PAPER

STANDARDIZED UXO DEMONSTRATION SITES

NAVAL RESEARCH LABORATORIES MULTI-SENSOR TOWED ARRAY DETECTION SYSTEM
(MTADS) (GEM-3) - OPEN FIELD SCORING RECORD NO. 245



The MTADS GEM-3 detection platform was demonstrated by Naval Research Laboratories of Washington, D.C., at Yuma Proving Ground, Arizona.

**The MTADS GEM-3
detection platform
was demonstrated by Naval Research
Laboratories (NRL) at the Yuma Proving
Grounds open field area. This technical
paper contains the results of that
demonstration. This is a reference document
only and does not serve as an endorsement
of the demonstrator's product by the
US Army or the Standardized UXO
Technology Sites Program.**



Technologies under development for the detection and discrimination of unexploded ordnance (UXO) require testing so that their performance can be characterized. To that end, standardized test sites have been developed at Aberdeen Proving Ground, Maryland, and Yuma Proving Ground, Arizona. These test sites provide a diversity of geology, climate, terrain, and weather as well as diversity in ordnance and clutter. Testing at these sites is independently administered and analyzed by the government for the purposes of characterizing technologies, tracking performance with system development, comparing performance of different systems, and comparing performance in different environments.

The Standardized UXO Technology Demonstration Site Program is a multi-agency program spearheaded by the US Army Environmental Center. The US Army Aberdeen Test Center and the US Army Corps of Engineers Engineering Research and Development Center provide programmatic support. The program is being funded and supported by the Environmental Security Technology Certification Program, the Strategic Environmental Research and Development Program, and the Army Environmental Quality Technology Program.

DEMONSTRATOR'S SYSTEM AND DATA PROCESSING DESCRIPTION

The MTADS GEM-3 is composed of three 96-cm diameter frequency-domain electromagnetic interference (EMI) sensors mounted in a triangular array. The array is mounted on a 3.5-meter long platform that is pulled by the MTADS tow vehicle. The sensor-transmit electronics and signal analog to digitals are located on the tow platform just in front of the sensor coils; the remaining sensor electronics are rack-mounted in the tow vehicle. Also mounted on the tow platform are three Global Positioning System (GPS) antennae and an International Measurement Unit (IMU).

Each of the three sensors in the array sequentially transmits a composite waveform made up of 10 frequencies logarithmically spaced from 30 Hz to just over 20 kHz for one base period (1/30 s). Thus, only one complete cycle of the 30 Hz frequency is transmitted, while many thousands of cycles of the highest frequency are transmitted. The current drives both a transmit coil and a counter-wound bucking coil. This sets up a "magnetic cavity" inside the bucking coil, in which a receive coil is placed. The current induced in this receive coil by the induced fields in buried metal targets is detected, digitized, and frequency-resolved during the two subsequent base periods while the other array sensors are transmitting. The detected signal is compared to the transmitted current and reported relative to the transmit current (parts per million) as both an in-phase and a quadrature component.

The 20 measured responses (in-phase and quadrature at 10 frequencies) make up the EMI Spectrum of the buried targets. These spectra can be analyzed by fitting to empirical functions, comparing against known library spectra, or fitting to target response coefficients. All three of these analysis methodologies will be applied to the data collected in this demonstration, and their results will be compared.

The MTADS GEM-3 consists of three, 96 cm diameter sensors arranged in a triangle. The array is pulled by the MTADS tow vehicle over the site at approximately 3 miles per hour. Lane spacing is the width of the MTADS tow vehicle, approximately 1.75 meters. Data are recorded from the array at approximately 9.7 Hz. This results in a down-track sampling interval of -15 cm and a cross-track sampling interval of 50 cm. For the measurements at Aberdeen Proving Ground, data will be recorded while traversing the test field in two orthogonal directions (roughly north to south and east to west). As part of the analysis, the extra classification performance (if any) that results from these extra data will be determined.

Individual sensors in the array are located using a three-receiver, real-time kinematics (RTK) GPS system. From this set of receivers, the position of the master antenna is recorded at 20 Hz, and the vectors to the other two antennae are recorded at 10 Hz. All positions are recorded at full RTK precision, -2-5 cm. In addition, the output of a full 6-axis IMU at 80 Hz is recorded to give complementary information on platform pitch and roll. All sensor readings are referenced to the GPS PostPostscriptum (1-PPS) output so that the precision of the GPS measurements can be utilized to full advantage.

The individual data streams into the data acquisition computer, running a custom variant of the WinGEM program called WinGEMArray, are each recorded in a separate file. These individual data files, which share a root name corresponding to the date and time the survey was initiated, include three sensor data files, four GPS files – one containing the National Maritime Electronics Association GGK sentences corresponding to the position of the master antenna and an automatic volume recognition (AVR) sentence giving one of the vectors to the secondary antennae, a second containing the second AVR sentence, a third containing the universal time coordinated time tag, and the fourth containing the computer time-stamped arrival of the GPS PPS – and one file for the IMU output. The sensor and GPS files are in American Standard Code for Information Interchange (ASCII) format, and the IMU file mirrors the packed binary output of the IMU.

PERFORMANCE SUMMARY

Results for the open field test broken out by size, depth and nonstandard ordnance are presented in the Summary of results table. Results by size and depth include both standard and nonstandard ordnance. The results by size show how well the demonstrator did at detecting/discriminating ordnance of a certain caliber range. The results are relative to the number of ordnance items emplaced. Depth is measured from the geometric center of anomalies.

The response stage results are derived from the list of anomalies above the demonstrator-provided noise level. The results for the discrimination stage are derived from the demonstrator's recommended threshold for optimizing UXO field cleanup by minimizing false digs and maximizing ordnance recovery. The lower 90 percent confidence limit on probability of detection and P_{fp} was calculated assuming that the number of detections and false positives are binomially distributed random variables. All results have been rounded to protect the ground truth. However, lower confidence limits were calculated using actual results.

OPEN FIELD SCORING SUMMARY

Metric	Overall	Standard	Non-Standard	By Size			By Depth, m		
				Small	Medium	Large	< 0.3	0.3 to <1	>= 1
RESPONSE STAGE									
P _d	0.80	0.80	0.80	0.80	0.75	0.90	0.80	0.80	0.50
P _d Low 90% Conf	0.76	0.75	0.75	0.74	0.69	0.83	0.79	0.76	0.38
P _{fp}	0.80	-	-	-	-	-	0.80	0.80	0.30
P _{fp} Low 90% Conf	0.76	-	-	-	-	-	0.76	0.76	0.12
BAR	0.00	-	-	-	-	-	-	-	-
DISCRIMINATION STAGE									
P _d	0.75	0.75	0.75	0.75	0.70	0.85	0.70	0.80	0.45
P _d Low 90% Conf	0.72	0.70	0.72	0.70	0.65	0.78	0.73	0.74	0.35
P _{fp}	0.65	-	-	-	-	-	0.60	0.75	0.30
P _{fp} Low 90% Conf	0.63	-	-	-	-	-	0.58	0.72	0.12
BAR	0.00	-	-	-	-	-	-	-	-

Response Stage Noise Level: 1.20

Recommended Discrimination Stage Threshold: 14.86

Note: The recommended stage threshold values are provided by the demonstrator.

