



TECHNICAL PAPER

# STANDARDIZED UXO DEMONSTRATION SITES

## TETRA TECH FOSTER WHEELER, INC. – EM61/SLING

*WOODS SCORING RECORD NO. 457*

**T**echnologies under development for the detection and discrimination of unexploded ordnance (UXO) require testing so that their performance can be characterized. To that end, Standardized Test Sites have been developed at Aberdeen Proving Ground (APG), Maryland and Yuma Proving Ground (YPG), Arizona. These test sites provide a diversity of geology, climate, terrain, and weather as well as diversity in ordnance and clutter. Testing at these sites is independently administered and analyzed by the government for the purposes of characterizing technologies, tracking performance with system development, comparing performance of different systems, and comparing performance in different environments.

The Standardized UXO Technology Demonstration Site Program is a multi-agency program spearheaded by the U.S. Army Environmental Center (USAEC). The U.S. Army Aberdeen Test Center (ATC) and the U.S. Army Corps of Engineers Engineering Research and Development Center (ERDC) provide programmatic support. The program is being funded and supported by the Environmental Security Technology Certification Program (ESTCP), the Strategic Environmental Research and Development Program (SERDP) and the Army Environmental Quality Technology Program (EQT).

### DEMONSTRATOR'S SYSTEM AND DATA PROCESSING DESCRIPTION

The EM61 MKII uses time domain technology to facilitate the detection and discrimination of metallic objects. Two coils 100 by 100 cm are oriented in a horizontal coplanar fashion and separated by a vertical distance of 40-cm. The system is utilized either on nonmagnetic wheels or as a man-portable unit (terrain-dependent) with the lower coil 40 cm above the ground surface. In general, a transmit pulse of uni-polar rectangular current (25 percent duty) of very short duration is applied to the lower coil. This primary current creates a primary magnetic field that induces eddy currents in nearby metal objects. The current flowing in the metal object creates a secondary magnetic field that is detected by both the lower and upper coils. The transmitter pulse frequency is 75 Hertz (Hz), the pulse duration is 3.3 milliseconds, the peak power output is 50 watts, and the average power is 25 watts. Both coils possess zero decibels of gain.

The secondary magnetic field created by metal objects is sampled by the EM61 MKII electronics, which reside in the backpack, at times of 216 microseconds ( $\mu$ s), 366  $\mu$ s, 660  $\mu$ s on the bottom coil and 660  $\mu$ s on the top coil after the turn-off of the transmit pulse. Digital data for these four individual time gates are integrated and recorded to a Juniper Allegro field computer at a rate of 12 Hz. The individual time gate data are converted into units of millivolts (mV), normalized, and gain is applied to each time gate by the EM61MK2A



The EM61 in the sling platform is shown as demonstrated by Tetra Tech Foster Wheeler, Inc. at Aberdeen Proving Ground, Maryland.

The EM61  
in the sling platform  
was demonstrated by Tetra Tech Foster  
Wheeler, Inc. (TtFW) at the Aberdeen  
Proving Ground Standardized  
Demonstration Site's Woods Area.  
This technical paper contains  
the results of that demonstration.  
This is a reference document only and  
does not serve as an endorsement of  
the demonstrator's product by the  
US Army or the Standardized UXO  
Technology Sites Program.

### For more information

US Army Environmental Center  
Public Affairs Office  
410-436-2556, fax 410-436-1693  
e-mail: [usaecpao@aec.apgea.army.mil](mailto:usaecpao@aec.apgea.army.mil)  
<http://aec.army.mil>  
<http://www.uxotestsites.org>

software v1.22 on the Juniper Allegro field computer.

Safety hazards for the EM61 MKII equipment include electromagnetic radiation. The electromagnetic field of the system could potentially detonate some types of specialized ordnance. The Hazards of Electromagnetic Radiation to Ordnance (HERO) distance for the EM61 MKII is 20 cm. USACE recommends a ground clearance of at least 40 cm when electrically fuzed ordnance is present.

The CST consists of four laser transmitters and a field computer for logging the position data via wireless modem. Four Trimble Spectra Precision LS920 Laser Transmitters are positioned in a diamond or square geometry over 1/2 to 1 acre depending upon the tree density. The transmitters are leveled, and an automatic routine calculates the relative x-y-z plane between the transmitters to a tolerance of 1 inch or less. A laser detector wand (i.e., receiver) is centered over the EM61 MKII coils on a TtFW-designed fiberglass doghouse. The detector wand receives the laser pulses from the four transmitters simultaneously, and computes a position based on the known position of the laser transmitters. Only two of the laser transmitters are necessary to compute a reliable position to a relative accuracy of approximately 1 inch. The position data are updated at 2 to 3 Hz and sent via wireless modem to the field computer for storage.

The Leica Series 1100 RTS consists of a laser-based total station survey instrument (transmitter), prism (receiver), and RCS 100 remote control. The transmitter is positioned over a ground position point of known location, and an x-y-z Cartesian coordinate system is defined by occupying an additional known ground position with the receiver prism. The receiver prism is mounted on a TtFW doghouse centered over the EM61 MKII coils, and the RTS automatically tracks the prism at distances of several thousand feet to an accuracy of approximately 1 inch.

## PERFORMANCE SUMMARY

Results for the Wooded test, broken out by size, depth and nonstandard ordnance, are presented below. Results by size and depth include both standard and nonstandard ordnance. The results by size show how well the demonstrator did at detecting/discriminating ordnance of a certain caliber range. The results are relative to the number of ordnances emplaced. Depth is measured from the geometric center of anomalies.

The Response Stage results are derived from the list of anomalies above the demonstrator-provided noise level. The results for the Discrimination Stage are derived from the demonstrator's recommended threshold for optimizing UXO field cleanup by minimizing false digs and maximizing

ordnance recovery. The lower 90-percent confidence limit on probability of detection and probability of false positive was calculated assuming that the number of detections and false positives are binomially distributed random variables. All results have been rounded to protect the ground truth. However, lower confidence limits were calculated using actual results.

## SUMMARY OF WOODED RESULTS FOR EM61/SLING

Metric	Overall	Standard	Nonstandard	By Size			By Depth, m		
				Small	Medium	Large	< 0.3	0.3 to <1	>= 1
<b>RESPONSE STAGE</b>									
P <sub>2</sub>	0.50	0.50	0.45	0.40	0.60	0.55	0.60	0.40	0.20
P <sub>2</sub> Low 90% Conf	0.43	0.43	0.38	0.34	0.50	0.38	0.52	0.34	0.07
P <sub>2</sub> Upper 90% Conf	0.54	0.56	0.57	0.48	0.69	0.71	0.66	0.52	0.35
P <sub>10</sub>	0.50	-	-	-	-	-	0.50	0.60	0.30
P <sub>10</sub> Low 90% Conf	0.49	-	-	-	-	-	0.44	0.54	0.19
P <sub>10</sub> Upper 90% Conf	0.55	-	-	-	-	-	0.54	0.63	0.42
BAR	0.15	-	-	-	-	-	-	-	-
<b>DISCRIMINATION STAGE</b>									
P <sub>2</sub>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P <sub>2</sub> Low 90% Conf	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P <sub>2</sub> Upper 90% Conf	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
P <sub>10</sub>	N/A	-	-	-	-	-	N/A	N/A	N/A
P <sub>10</sub> Low 90% Conf	N/A	-	-	-	-	-	N/A	N/A	N/A
P <sub>10</sub> Upper 90% Conf	N/A	-	-	-	-	-	N/A	N/A	N/A
BAR	N/A	-	-	-	-	-	-	-	-

Response Stage Noise Level: 0.00

Recommended Discrimination Stage Threshold: 0.00

*Note: The recommended discrimination stage threshold values are provided by the demonstrator. No discrimination algorithm was applied. Therefore, the discrimination stage results are not applicable.*

To view the full Scoring Record for this demonstration and for all other demonstrations conducted at the Aberdeen and Yuma Proving Grounds in support of the Standardized UXO Technology Demonstration Sites Program please visit our Web site at: [www.uxotestsites.org](http://www.uxotestsites.org).

