



TECHNICAL PAPER

STANDARDIZED UXO DEMONSTRATION SITES

NAEVA GEOPHYSICS, INC. – EM61 MKII/MAN-PORTABLE

WOODS SCORING RECORD NO. 494



The EM61 MKII in the man-portable platform is shown being demonstrated by NAEVA at Aberdeen Proving Ground, Maryland.

Technologies under development for the detection and discrimination of unexploded ordnance (UXO) require testing so that their performance can be characterized. To that end, Standardized Test Sites have been developed at Aberdeen Proving Ground (APG), Maryland and Yuma Proving Ground (YPG), Arizona. These test sites provide a diversity of geology, climate, terrain, and weather as well as diversity in ordnance and clutter. Testing at these sites is independently administered and analyzed by the government for the purposes of characterizing technologies, tracking performance with system development, comparing performance of different systems, and comparing performance in different environments.

The Standardized UXO Technology Demonstration Site Program is a multi-agency program spearheaded by the U.S. Army Environmental Center (USAEC). The U.S. Army Aberdeen Test Center (ATC) and the U.S. Army Corps of Engineers Engineering Research and Development Center (ERDC) provide programmatic support. The program is being funded and supported by the Environmental Security Technology Certification Program (ESTCP), the Strategic Environmental Research and Development Program (SERDP) and the Army Environmental Quality Technology Program (EQT).

DEMONSTRATOR'S SYSTEM AND DATA PROCESSING DESCRIPTION

In an effort to maintain the highest standards for quality data acquisition in an area suspected to have small munitions, the EM61 will be operated in a litter/strecher configuration, where the coils are supported by 12-foot long fiberglass poles and transported by two operators. The data logger and backpack will be controlled by the operator at the back of the system. Coil height, consistent with the towed-array at 40cm, will be maintained through the use of harnesses worn by both operators. NAEVA has found data quality in the tandem configuration to be superior to wheeled operation in all but the smoothest terrain.

The EM61 is a time-domain electromagnetic instrument designed to detect, with high spatial resolution, shallow ferrous and non-ferrous metallic objects. The applicability of the instrument for Ordnance and Explosives (OE) detection has been widely demonstrated at sites across the United States. Each instrument consists of two air-cored coils (1m x 0.5m), batteries, processing electronics, and a digital data recorder. The larger of the two coils functions as the electromagnetic (EM) source and receiver and is positioned 40 cm below a second receiver coil. Secondary currents induced in both coils are measured in millivolts (mV).

Geonics has recently updated their standard EM61 system to the EM61 MKII. The primary difference in the MKII system is the use of multiple

The EM61 MKII
in the man-portable platform
was demonstrated by NAEVA at the
Aberdeen Proving Ground Standardized
Demonstration Site's Woods Area.
This technical paper contains
the results of that demonstration.
This is a reference document only and
does not serve as an endorsement of
the demonstrator's product by the
US Army or the Standardized UXO
Technology Sites Program.

For more information

US Army Environmental Center
Public Affairs Office
410-436-2556, fax 410-436-1693
e-mail: usaecpao@aec.apgea.army.mil
<http://aec.army.mil>
<http://www.uxotestsites.org>

time-gates; the time after the electromagnetic pulse is generated that the receiver coil measures the response. Standard EM61's offer a single time-gate in both the bottom and the top coils. While the top coil time-gate is unchanged, the MKII records early, middle, and late channels from the bottom coil. The late time-gate (third channel) corresponds to the standard EM61 while the earlier time-gates offer enhanced capabilities for the detection of smaller metallic objects. Data from all three channels will be stored and processed during the demonstrations at APG.

PERFORMANCE SUMMARY

Results for the Woods test broken out by size, depth and nonstandard ordnance are presented in table below. Results by size and depth include both standard and nonstandard ordnance. The results by size show how well the demonstrator did at detecting/discriminating ordnance of a certain caliber range. The results are relative to the number of ordnance items emplaced. Depth is measured from the geometric center of anomalies.

The Response Stage results are derived from the list of anomalies above the demonstrator-provided noise level. The results for the Discrimination Stage are derived from the demonstrator's recommended threshold for optimizing UXO field cleanup by minimizing false digs and maximizing ordnance recovery. The lower 90 percent confidence limit on probability of detection and P_{fd} was calculated assuming that the number of detections and false positives are binomially distributed random variables. All results have been rounded to protect the ground truth. However, lower confidence limits were calculated using actual results.

SUMMARY OF WOODED RESULTS FOR EM61 MKII/MAN-PORTABLE

Metric	Overall	Standard	Nonstandard	By Size			By Depth, m		
				Small	Medium	Large	< 0.3	0.3 to <1	>= 1
RESPONSE STAGE									
P _d	0.50	0.55	0.45	0.40	0.05	0.00	0.55	0.45	0.25
P _d Low 90% Conf	0.45	0.47	0.35	0.32	0.54	0.43	0.49	0.38	0.11
P _d Upper 90% Conf	0.55	0.60	0.53	0.47	0.72	0.75	0.64	0.57	0.42
P _{fa}	0.55	-	-	-	-	-	0.50	0.60	0.20
P _{fa} Low 90% Conf	0.50	-	-	-	-	-	0.45	0.55	0.12
P _{fa} Upper 90% Conf	0.56	-	-	-	-	-	0.56	0.63	0.32
BAR	0.05	-	-	-	-	-	-	-	-
DISCRIMINATION STAGE									
P _d	0.20	0.25	0.20	0.15	0.25	0.30	0.25	0.20	0.10
P _d Low 90% Conf	0.18	0.18	0.13	0.12	0.19	0.17	0.21	0.12	0.03
P _d Upper 90% Conf	0.27	0.30	0.28	0.24	0.36	0.47	0.34	0.27	0.28
P _{fa}	0.30	-	-	-	-	-	0.30	0.30	0.05
P _{fa} Low 90% Conf	0.25	-	-	-	-	-	0.26	0.26	0.00
P _{fa} Upper 90% Conf	0.31	-	-	-	-	-	0.35	0.34	0.11
BAR	0.00	-	-	-	-	-	-	-	-

Response Stage Noise Level: 1.50
 Recommended Discrimination Stage Threshold: 308.50

Note: The recommended discrimination stage threshold values are provided by the demonstrator.

To view the full Scoring Record for this demonstration and for all other demonstrations conducted at the Aberdeen and Yuma Proving Grounds in support of the Standardized UXO Technology Demonstration Sites Program please visit our Web site at: www.uxotestsites.org.